

Exam : **NS0-301**

Title : Network Appliance Certified
Solution Architect-SAN

Version : DEMO

1. When running in standby cfmodes, if the host can no longer access the LUNs from Controller A after an array controller failover to Controller B, what two things should you check? (Choose two.)

A.The cabling between the storage controller and the switch.

B.The zoning on the switch.

C.The LUN masking on the storage controller.

D.The persistent bindings.

Answer: AB

2. What could a G_Port represent?

A.A Fibre Channel hub's connection to the FC switch.

B.A storage controller's connection to the FC switch.

C.An inter-switch link connection between FC switches.

D.An unused port on the FC switch.

Answer: D

3. What type of zoning is based on the physical port you are connected to?

A.hard

B.port

C.soft

D.physical

Answer: A

4. Which characteristic differentiates an iSCSI HBA from a NIC card?

A.larger frame size

B.2 Gb/s rate

C.link aggregation

D.TCP offload

Answer: D

5. Which two are advantages of an IP SAN as it compares to FC SAN? (Choose two.)

A.It uses well-understood technologies such as SCSI and Ethernet.

B.It provides faster failover.

C.It has lower cost per switch port.

D.It provides lower propagation delay.

Answer: AC

6. Select the appropriate IP protocol that uses Service Location Protocol (SLP) protocol for discovery and management.

A.iFCP

B.FCIP

C.iSCSI

D.AoE

Answer: C

7. Which three are benefits of both FC and iSCSI SAN? (Choose three.)

A.Enables storage consolidation.

B.Servers can be backed up to the same Tape Library or VTL.

C.Enables server consolidation.

D.Disk Arrays appear as autonomous file servers.

Answer: ABC

8. Select two advantages an iSCSI SAN has over a Fibre Channel SAN. (Choose two.)

A.An iSCSI SAN can take advantage of existing IP infrastructure components.

B.An iSCSI SAN provides a more affordable solution for cost-sensitive environments.

C.An iSCSI SAN has lower latency than a Fibre Channel SAN.

D.An iSCSI SAN provides higher storage utilization than a Fibre Channel SAN.

Answer: AB

9. The only way to implement iSCSI is by using an iSCSI HBA. (True or False?)

A. True

B. False

Answer: B

10. Which three are performance tuning parameters available for Fibre Channel HBAs on a host?

(Choose three.)

A.HBA queue depth

B.Fibre Channel speed

C.frame size

D.LUN device ID

Answer: ABC

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.